

WR100 (100A) For Winding Resistance measurements

© ABB

2 or 3 measuring channels. Fastest discharge unit on market.
3 temperature channels. Heavy duty protection circuitry. Demagnetisation circuit. Internal «Heat run test» software available. USB interfaces. Color touch screen.

Resistance range	0.00 $\mu\Omega$ to 100 k Ω
Accuracy	$\pm 0.1\%$ Rdg
Resolution	5 Digits or 0.05 $\mu\Omega$
Current range	25 mA ... 100A/50V DC
Inductance range	up to 1500 Henry
Operating range	-10°C to 60°C
Weight	21.9 kg (48.3 lbs.)
Input power	90 to 264 VAC (3 kW max.) 47... 63 Hz



Measurement Parameters

Current Range	Measuring Range	Accuracy	Resolution
30 – 100 A	0.00 $\mu\Omega$... 1.7 Ω	$\pm 0.1\%$ Rdg $\pm 0.05 \mu\Omega$	5 Digits or 0.05 $\mu\Omega$
15 – 30 A	0.0 $\mu\Omega$... 3.3 Ω	$\pm 0.1\%$ Rdg $\pm 0.1 \mu\Omega$	5 Digits or 0.1 $\mu\Omega$
8 – 15 A	0.0000 m Ω ... 6.3 Ω	$\pm 0.1\%$ Rdg $\pm 0.2 \mu\Omega$	5 Digits or 0.2 $\mu\Omega$
3 – 8 A	0.0000 m Ω ... 16.7 Ω	$\pm 0.1\%$ Rdg $\pm 0.5 \mu\Omega$	5 Digits or 0.5 $\mu\Omega$
1 – 3 A	0.000 m Ω ... 47.2 Ω	$\pm 0.1\%$ Rdg $\pm 1 \mu\Omega$	5 Digits or 1 $\mu\Omega$
0.7 – 1 A	0.000 m Ω ... 71.4 Ω	$\pm 0.1\%$ Rdg $\pm 2 \mu\Omega$	5 Digits or 2 $\mu\Omega$
0.3 – 0.7 A	0.000 m Ω ... 167 Ω	$\pm 0.1\%$ Rdg $\pm 5 \mu\Omega$	5 Digits or 5 $\mu\Omega$
0.1 – 0.3 A	0.00 m Ω ... 500 Ω	$\pm 0.1\%$ Rdg $\pm 10 \mu\Omega$	5 Digits or 10 $\mu\Omega$
25 – 100mA	0.00 m Ω ... 2 k Ω	$\pm 0.1\%$ Rdg $\pm 20 \mu\Omega$	5 Digits or 20 $\mu\Omega$
– 25mA	2 k Ω ... 10 k Ω	$\pm 0.2\%$ Rdg $\pm 200 m\Omega$	5 Digits or 200 m Ω
– 25mA	10 k Ω ... 100 k Ω	$\pm 0.8\%$ Rdg $\pm 20 \Omega$	4 Digits or 20 Ω

Accessories

- Current cables 2 x 10 meters
- Potential cables CH1 2 x 10 meters
- Potential cables CH2 2 x 10 meters
- Jumper cable 10 meters
- Instruction manual
- T-Base Pro software for data exchange and analysis

Specifications

Model with 2 channels
WR100-12R (rackmount unit)

Model with 3 channels
WR100-13R (rackmount unit)

Size (field case)
L: 490 mm (19.3")
W: 436 mm (17.2")
H: 310 mm (12.2")

Weight
21.9 kg (48.3 lbs.)

Interface
4 USB 2.0 full speed (3 host, 1 device)
and 9 Pin RS232 serial

Memory Storage
Internally stores up to 10 000 test results

Panel Display
5.7" Color LCD with LED back lighting
and touch screen

Front Panel
Sealed, Anodized

Options

- WRO 112
10m cable extension set
- TP 01
External temperature probe
- TP 03
External temperature probes
- Extension for T-Base Pro software
Remote Control
Fully automatic test sequences
- AHRT 01
Automatic heat run test software
- MUX R Multiplexer

